Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Vibia Lighting, progres 4-6, 08850 Gava gava Barcelona, ES

Model identifier: 032504/1B

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

ing control

776-0-100-0-0-0-0-0-0-0-0-0-0-0-0-0-0-0-0-					
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS	
Light source cap	o-type	Renobable PCB			
(or other electri	ic interface)				
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable	e light source:	No	Envelope:	-	
High luminance	light source:	No			
Anti-glare shield	d:	No	Dimmable:	Yes	
		Product para	meters		
Parameter		Value	Parameter	Value	
		General product p	arameters:		
_ ·	nption in on- 00 h), rounded st integer	24	Energy efficiency class	E	
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	2 910 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode pow pressed in W	ver (P _{on}), ex-	24,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,10	
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90	
Outer dimen-	Height	530	Spectral power dis-	See image	
sions without	Width	400	tribution in the	in last page	
separate con- trol gear, light-	Depth	2 000	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,458		
		nates (x and y)	0,413		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	46	Survival factor	-		
the lumen maintenance factor	-				

(a)'-': not applicable; (b)'-': not applicable;

