Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Vibia	Supplier'	s name	or trade	mark:	Vibia
--------------------------------------	-----------	--------	----------	-------	-------

Supplier's address: Vibia Lighting, progres 4-6, 08850 Gava gava Barcelona, ES

Model identifier: 034504/1B

_	•			
Ivpe	ot	light	source	

sions without

separate con-

trol gear, light-

control

ing

Width

Depth

Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		Renobable PCB				
(or other electric interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable I	ight source:	No	Envelope:	-		
High luminance li	ght source:	No				
Anti-glare shield:		No	Dimmable:	Yes		
	Product parameters					
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumpt mode (kWh/1000 up to the nearest	O h), rounded	4	Energy efficiency class	E		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		485 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power (P _{on}), expressed in W		4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,10		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90		
Outer dimen-	Height	2 000	Spectral power dis-	See image		

tribution

range 250 nm to 800

nm, at full-load

200

200

in the

in last page

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,458	
		nates (x and y)	0,413	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	46	Survival factor	-	
the lumen maintenance factor	-			

(a)'-': not applicable; (b)'-': not applicable;

