

NOTE: the stems of the Syphasera collection are made of brass protected for outdoor with black coloured varnish. They are suitable for outdoor use included immersion. Nevertheless, in case of installation into water, we recommend a version available on request designed for this kind of projects and requests.

Light source


LED bulb G4 12V DC 1x1,5W / energy class A+ / lumen 150 / K 2700 / CRI 85 / protection grade IP65

NOTE: IP specifics - lamp holder IP65 (not protected against immersion); wires and connectors IP68; drivers IP67; IP average rate of the lamp 44.

Power supply

12V DC transformer not included

Dimensions



cylinder with holder
Ø 1,5 x H 21 cm
H tot. 65 cm (cable 255 cm)
H tot. 80 cm (cable 240 cm)
H tot. 110 cm (cable 210 cm)
H tot. 140 cm (cable 180 cm)

Order code

SYS65 H 65 cm
SYS80 H 80 cm
SYS110 H 110
cm
SYS140 H 140
cm

**Accessories for
gel box system**

ED6 driver 10W 12V DC 220-240V IP67 not dimmable (max 6 lamps)
MB1 mini gel box IP68 (max 2 connections, connector included)
MB2 mini gel box IP68 (max 6 connections, connector included)
KP1 extension kit 5 mt with mini gel box IP68 (max 1 lamp)

**Accessories for
quick connectors
system**

ED6CR driver 10W 12V DC 220-240V IP67 not dimmable with quick connectors (max 6 lamps)
CRM multiple quick connector IP68 - 1 IN & 5 OUT (max 5 connections)
CRS single quick connector IN IP68
KP2 extension kit 5 mt with quick connectors IP68 (max 1 lamp)