## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name	or trade	mark:	Vibia
------------	------	----------	-------	-------

Supplier's address: Vibia Lighting, progres 4-6, 08850 Gava gava Barcelona, ES

Model identifier: 035004/1A

_	•			
Typa	Λt	liaht	sourc	Δ.
IVDE	OI.	IIGIIL	<b>3</b> Uui C	c.

ing control

Type of light 30	ui cc.			
Lighting techno	Lighting technology used:		Non-directional or directional:	NDLS
Light source cap	o-type	Renobable PCB		
(or other electri	ic interface)			
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	Yes
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	parameters:	
Energy consur mode (kWh/10 up to the neare	00 h), rounded	12	Energy efficiency class	E
dicating if it refo a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone errow cone (90º)	1 455 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pov pressed in W	ver (P <sub>on</sub> ), ex-	12,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,10
(P <sub>net</sub> ) for CLS,	tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90
Outer dimen-	Height	310	Spectral power dis-	See image
sions without	Width	2 000	tribution in the	in last page
separate con- trol gear, light-	Depth	2 000	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,458	
		nates (x and y)	0,413	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	46	Survival factor	-	
the lumen maintenance factor	-			

(a)'-': not applicable; (b)'-': not applicable;

