## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or t	t <b>rade mark:</b> Vibia
----------------------	---------------------------

Supplier's address: Vibia Lighting, progres 4-6, 08850 Gava gava Barcelona, ES

Model identifier: 167504/10

On-mode power (Pon),

Networked standby

(P<sub>net</sub>) for CLS, expressed in W

and rounded to the second dec-

Height

Width

Depth

power

pressed in W

Outer dimen-

sions without

separate con-

trol gear, light-

control

imal

ing

_	•			
Tyna	Ot.	lioht	sour	CD.
IVDC	O.	IIGIIL	30ui	LC.

Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Renobable PCB		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
	Product parar	meters	
Parameter	Value	Parameter	Value
	General product p	arameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	4	Energy efficiency class	Е
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	485 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temper-	2 700

4,0

100

150

60

atures, rounded to the nearest 100 K, that can be set

Standby power (P<sub>sb</sub>),

expressed in W and

rounded to the sec-

Colour rendering in-

dex, rounded to the

nearest integer, or the range of CRI-val-

ues that can be set Spectral power dis-

range 250 nm to 800

nm, at full-load

in

the

ond decimal

tribution

Page 1 / 3

0,10

90

See image

in last page

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,458		
		nates (x and y)	0,413		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	46	Survival factor	-		
the lumen maintenance factor	-				

(a)'-': not applicable; (b)'-': not applicable;

